

**The most
sustainable
lighting
solution**

QL Induction Lighting Systems

QL induction lighting is used for professional, general and special lighting applications because of its unmatched durability and high luminous efficacy with excellent light quality. QL offers a nearly maintenance free operation and superior energy saving. Induction lamps have a unique long performance life up to 100,000 hours because there is no use of electrodes in the bulb. The lifetime of the system is determined at 80,000 hours, which equals approximately 20 years based on 4000 burning hours per year.

The major features of QL lamp systems, and their related benefits for the user, are:

Benefits

- Easy installation
- Good color rendering (Ra > 80) and choice of color temperature
- Useful light immediately after switch on
- Easy to use as retrofit or in new construction applications
- Economic, environment-friendly lighting in situations with long burning hours
- Lowest maintenance costs

Features

- Dimmable to 50%
- Crisp white light with no color shift.
- Operates in hot and cold environments - amalgam control.
- High lumen efficiency - 55W QL features 3,650 initial lumens.
- Also available in 85 and 165 watts.

Application

Ideal for street lighting, bridges and tunnels, hazardous areas, cold storage warehouses and hard-to-reach applications.

Compliances and approvals

- **Safety**
IEC 62532, IEC 61347-1, IEC 62471
- **Performance**
IEC 62639 (in prep.), IEC 60929
- **Quality standard**
ISO 9001
- **Environmental management system**
ISO 14001
- **Electromagnetic Compatibility**
EN 61000, EN 55015, EN 55022
- **Vibration and (thermal)shocks**
IEC 60068

QL 55W Lamp



PRODUCT DATA

Product number

Full product name

Pieces/sleeve

Sleeves per box

Net weight

Light Technical

Characteristics

Chromaticity Coordinate X

Chromaticity Coordinate Y

RA

Luminous Flux System

Luminous Efficacy System

Luminous Efficacy Lamp

Luminance Average EL

P.E.T.(NIOSH)



Damage Factor (Dfc)

QL05500027	QL05500030	QL05500040	QL05500050
QL Twist Base	QL Twist Base	QL Twist Base	QL Twist Base
55W 827	55W 830	55W 840	55W 850
1			
6			
0.137 kg per piece			

2700K	3000K	4000K	5000K
471	442	392	346
416	404	385	359
>80	>80	>80	>80
3550 lm	3650 lm	3650 lm	3500 lm
65 lm/W	66 lm/W	66 lm/W	64 lm/W
76 lm/W	78 lm/W	78 lm/W	74 lm/W
5.0 cd/cm ²	5.0 cd/cm ²	5.0 cd/cm ²	5.0 cd/cm ²
>24h	>24h	>24h	>24h
<0.6	<0.6	<0.6	<0.6


PHOTOMETRIC DATA

Spectral energy distribution




Typical Spectral energy distribution of QL 55W 3000K.

LIGHT DISTRIBUTION



Typical light distribution of QL 55W



Typical light distribution of QL 55W, Azimuth angle

QL 55W Power coupler

PRODUCT DATA

Product number

Product description

Pieces per box

Net weight

Characteristics

Storage temperature

Operating temperature

Operating Position

Safety approvals

EMC approvals

Cable length

Connectors

PC05500000

QL Power Coupler 55W

6

0.166 kg per piece

-40°C to +85°C

-40°C to +55°C_{ambient}

Universal

cULus and CE

Complies with all international EMC requirements

555 mm / 21.9 inch

N/A



For detailed information and guiding concerning the development of appropriate luminaire designs please visit our website www.qlcompany.com; "Information for Original Equipment" (OEM Guide).

Specifications subject to change without notice.



QL 55W Generator



PRODUCT DATA

Product number

Product description

Pieces per box

Net weight

Dimensions (L x W x H)

Connectors

Features

Dimming behavior

General Characteristics

Lifetime system

Efficiency

Cooling

Tcase

Storage

Operating temp.

Operating position

Safety approvals

EMC approvals

Electrical Characteristics

Input line freq.

Power Factor

Current THD

Output Voltage

Switching freq.

Current nom.

Run-up/short

Dimming

GE05523001	GE05512001
QL Generator 55W 200-277V	QL Generator 55W 100-120V
6	6
0.580 kg per piece	0.580 kg per piece
152 x 76 x 41 mm	152 x 76 x 41 mm
Cage clamp terminals	Cage clamp terminals

High reliability

Instant hot and cold (re) start

Operates in hot and cold environments


Dimmable to 50%

Can operate on both AC and DC power

Power Factor Correction and limited inrush current

Protection lamp end of life

Extended protection against mains faults and deviations



80.000 hrs at Tc=72°C

> 90%, max. load

convection, dependent on system set-up, heat sinking required

82°C max (72°C for full life)

-40°C to +85°C

-40°C to +55°C ambient

Universal

C-UL-US and CE

Complies with all international EMC requirements

45 - 66Hz

> 0.98

ANSI C82.11-2002

130 - 220 Vac

2.67 MHz ± 8%

Depending on lamp

< 1.8 x I_{nom}

EN60929, 1-10 V_{dc} analog, 50-100% output power

QL 55W System




DIMENSIONAL DRAWING

Product dimensions

Overall length C (Max)
 Length gear C3 (Norm)
 Diameter D (Max)
 Height gear H (Norm)
 Cable length X (Norm)

141 mm / 5.55 inch
154 mm / 6.06 inch
86 mm / 3.39 inch
40.8 mm / 1.61 inch
555 mm / 21.85 inch



SYSTEM DATA

General Characteristics

Operating Position
 Life System to 1% failures
 Life System to 3% failures
 Life System to 5% failures
 Life System to 10% failures

Universal
40,000 hr
60,000 hr
80,000 hr
100,000 hr

Electrical Characteristics

System Power
 Operating Frequency
 Ignition Time
 Run-up time 70%
 Re-ignition Time

55 W
2.650 MHz
0.5 sec
10 min
0.5 sec

Environmental Characteristics

Mercury (Hg) Content 5.0 mg

North America distribution and sales:

Nedap Light Controls USA
 14A Industrial Way
 Atkinson, NH 0381, USA
 Phone: 603 458 2089
 Fax: 603 458 5632
info@ql-inductionlighting.us
www.nedap-qlinduction.com

EMEA manufacturing and sales:

QL Company B.V.
 Philipsweg 1
 NL-6026 RA Maarheeze
 Phone: +31 88 1269170
 Fax: +31 88 1269199
sales@qlcompany.com
www.qlcompany.com

Asia-Pacific distribution and sales:

IMT Far East Pte Ltd
 22 Boon Lay Way
 #01-58 (Level2),
 Tradehub 21
 Singapore 609968
 Phone: +65 6341 5153
sales@qlcompany.com