



EcoVantage

EcoVantage 40W 120V G25 WH

The new EcoVantage bulbs reduce energy consumption without sacrificing the qualities of a traditional bulb. They uniquely produce light more efficiently. They work with dimmer switches and are available in the familiar A-shape design. Use them in existing fixtures just as you would standard incandescents and your home will look great while you save energy.

Product data

• General Characteristics

Base	Medium [Single Contact Medium Screw]
Bulb	G25
Bulb Finish	White
Operating Position	Universal [Any or Universal (U)]
Nominal Lifetime	2500 hr
Rated Lifetime (hours)	2500 hr
Rated Lifetime (years)	2.5 an

• Light Technical Characteristics

Color Rendering Index	95 Ra8
Color Temperature	2800 K
Color Temperature technical	2800 K
Initial lumen	500 Lm
Rated Luminous Flux	500 Lm

• Electrical Characteristics

Rated Wattage	40 W
Watts	40 W
Lamp Wattage Technical	40 W
Voltage	120 V
Lamp Current	0.33 A
Dimmable	Yes

Starting Time	0.0 s
Warm-up Time to 60% Light Outp	instant full light

• Environmental Characteristics

Energy Efficiency Label (EEL)	D
-------------------------------	---

• Measuring Conditions

Switching cycle	8000X
-----------------	-------

• Product Dimensions

Overall Length C	115 (max) mm
Diameter D	80 (max) mm

• Product Data


Product number	420851
Full product name	EcoVantage 40W 120V G25 WH
Short product name	40G25/EV/W 120V 12/1 TP
Pieces per Sku	1
eop_pck_cfg	12
Skus/Case	12
Bar code on pack	46677420857
Bar code on case	50046677420852
Logistics code(s)	925708036301
eop_net_weight_pp	0.001 kg

PHILIPS

Dimensional drawing

EcoVantage 40W 120V G25 WH

Product	C (Max)	D (Max)
EcoCl30 40W E26 120V G-25 WH	115	80



E26



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, June 10
data subject to change